
Subject to technical alterations and printing errors • First edition 01/2000; Revised 01/2012

Product Data Sheet Elastodrain® EL 202



Protection and drainage sheet with extremely high loadability; designed for use under driveways, access roads for fire brigades, parking areas, etc.





The EL 202-panels can be fixed with detachable connectors.

Features

- extremely high mechanical loadability
- step joint edging
- protection layer according to German Standard DIN 18 195
- drainage effect according to German Standard DIN 4095
- "spade resistant"
- reduces subsonic noise
- high stability even during storms
- quick and easy installation
- joint connector as accessory available

Technical Data

Elastodrain® EL 202

Compression moulded building protection and drainage sheet of solid, vulcanized rubber, with a rebated edge and one-sided stud structure. The boards can be interconnected with special EL 202-Connectors.

Colour: black
Height: ca. 19 mm
Stud height: ca. 12 mm
Number of studs: ca. 1200 /m²
Weight: ca. 18 kg/m²

Compressive strength

 $\begin{array}{lll} \text{at 10\% compression:} & \text{ca. 400 kN/m}^2 \\ \text{Shore-strength:} & \text{ca. 75 Shore A} \\ \text{Static foundation support module:} & \text{ca. 285 MN/m}^3 \end{array}$

Heat resistance: up to 200° C, briefly up to $> 250^{\circ}$ C

In-plane water flow capacity (EN ISO 12958):


Dimensions: ca. 1.00 m x 1.00 m

Accessories:

Rubber 2-hole Connector Order No. 3221

Application Example

"Driveway for Cars"



Slabs in chipping bedding

Filter Sheet PV Elastodrain® EL 202 Slip Sheet TGF 20

Roof construction with root resistant waterproofing

Specification Suggestion

Trafficable protection and drainage sheet of solid, vulcanized rubber, with a step joint edging and a one-sided stud structure, weight ca. 18 kg/m², stud height ca. 12 mm, total height ca. 19 mm, Shore-strength 75 Shore A, static foundation support module ca. 285 MN/m³, inplane water flow capacity tested

according to EN ISO 12958, delivery and installation to manufacturer's instructions, to be fixed with two detachable connectors per meter.

Make: ZinCo Elastodrain® EL 202 Enquiries: ZinCo Canada Inc Phone: 1-905-6901-661

