Subject to technical alterations and printing errors • First edition 11/2011; Revised 01/201

Product Information Floraset® FS 75



Multi-functional drainage element of expanded polystyrene, for the application on extensive and intensive green roofs on both flat and pitched roofs.

Technical Data

Floraset® FS 75

Stable drainage element of expanded polystyrene (EPS); produced without CFC's.

 Material:
 EPS

 Colour:
 white

 Height:
 ca. 75 mm

 Weight:
 ca. 1.0 kg/m²

 Density:
 ca. 23 kg/m³

Compressive strength

at 10% compression: ca. 25 kN/m²

In-plane water flow capacity:

- on flat-roofs (large studs facing downwards):

roof slope 1%: ca. 0.7 l/(s·m) roof slope 2%: ca. 1.0 l/(s·m) roof slope 3%: ca. 1.3 l/(s·m)

- on pitched roofs (large studs facing upwards):

roof slope 10%: ca. 2.2 l/(s·m)


Dimension: ca. 1.00 m x 1.00 m

Features

- environmentally friendly produced without CFC's
- above the German Standard DIN 4095
- can be used on both sides
- large studs facing down: for 0°- roofs; also allows water dam-up
- small studs facing down: for sloped roofs with up to 20° inclination and for lightweight green roof on flat roofs
- pressure-resistant; quick and easy installation

Application Example

"0° - Roof and Pitched Roof"



Specification Suggestion

Drainage element of expanded polystyrene, density ca. 23 kg/m³, with water storage cells and multi-directional channel system on both sides, height ca. 75 mm, weight ca. 1.0 kg/m², compressive strength up to 25 kN/m², In-plane water flow capacity

ca. 1.0 l/(s·m) at 2% roof slope, delivery and installation according to manufacturer's instruction.

Make: ZinCo Floraset® FS 75 Enquiries: ZinCo Canada Inc. Phone: 1-905-690-1661

